FLY

Individual work platform rails 360° and wide steps.

Meets the new european standard EN 131-7 of individual work platforms that offer 360° protection. It is equipped with a fold stabilizer system can work so that it folded along a wall. Equipped with wide steps on the ascent ramp.

TECHNICAL

- The stabilizers can be closed to work in confined spaces;
- · Patented handrail;
- Leaflets with one gesture, allow to deploy a minimum space;
- · Transport wheels of 150 mm in diameter;
- · Ramp 55 cm wide rise;
- · Tool holder exchange;
- · Hinges in steel;
- · Packed in plastic;
- · Terms retractable;
- · Capacity: 150 kg.

EQUIPMENT

- Enhanced aluminum-slip deck (60x53 cm) with accidental system anti-opening and bottom 10 cm;
- The support tacos are PVC ergonomic non-slip;
- · Steps nonskid 80 mm distance between steps 26 cm;
- · Guard rails 100 cm in four sides;
- Closed folding and telescopic stabilizers 72 cm
 3/4 deg: open = 152 cm
 5/6 deg: open = 176 cm
 7/8 deg: open = 210 cm;
- · Anti-opening strap (enclosed stairway);
- Closed the ladder keeps his feet only (46 cm thickness).















REF		<u> </u> _	$\frac{1}{m}$	A_m		m m	KG	€
10866	3	1.99	0.75	2.75	0.72×1.34	0.46	24.00	
10867	4	2.25	1.00	3.00	0.72x1.55	0.46	26.00	
10868	5	2.55	1.26	3.26	0.72×1.78	0.46	27.00	
10869	6	2.83	1.52	3.52	0.72x1.99	0.46	29.00	
10870	7	3.11	1.78	3.78	0.72x2.25	0.46	30.00	
10871	8	3.39	2.03	4.03	0.72x2.46	0.46	32.00	











